


JS912 | Côtes de Sertissage

Crimping diameters



Côtes de sertissages téléchargeables sur : www.bjflex.com

TOLERANCE SERTISSAGE : 0 / - 0.3

Diamètre Tuyau	JUPES Ø X long	Paramètres Sertissage	TUYAU / HOSES									
			2SNK	R2A	R2AT	SPC2	SPC3	R9R	4SH	ULTRA	XTRA	
DN06 1/4	JS91206 Ø 22x30.5	Lg Dénudage	Sans	23	23				23			
		Ø serti	18.2	17.9	17.9				19.4			
DN10 3/8	JS91210 Ø 26X33	Lg Dénudage	Sans	26	26			26	26			
		Ø serti	22.9	22.5	22.8			20.9	23.5			
DN13 1/2	JS91213 Ø 30X37	Lg Dénudage	Sans	28	28			28	28			28
		Ø serti	25.7	25.2	25.2			26.2	25.3			25.9
DN16 5/8	JS91216 Ø 32X44	Lg Dénudage	Sans	33	33	33	33	33	33			33
		Ø serti	28.4	27.5	28.1	27.6	29.0	29.3				29.7
DN19 3/4	JS91219 Ø 38X49	Lg Dénudage	Sans	39	39			39	39	39	39	39
		Ø serti	33.3	33.5	33.5			33.3	33.8	33.7	34.3	33.7
DN25 1"	JS91225 Ø 46X58	Lg Dénudage	Sans	46	46			46	46	46	46	46
		Ø serti	42.5	40.8	40.9			41.5	41.3	41.2	41.7	41.7
DN32 1"1/4	JS91232 Ø 56X63	Lg Dénudage		51	51				51	51	51	
		Ø serti		49.5	49.5				50.9	48.8	49.2	
DN38 1"1/2	JS91238 Ø 64X72	Lg Dénudage		58	58				58	58		
		Ø serti		57.2	57.2				59.1	57.4		
DN50 2"	JS91250 Ø 76X78	Lg Dénudage		62	62				62	62		
		Ø serti		69.0	69.0				71.3	69.8		

Attention : les valeurs sont données à titre indicatif, contrôle à la pige de la déformation du nipple

www.bjflex.com